

Rated voltage 300/500 V



CONSTRUCTION

| | |
|-----------------------|--|
| Standard | SFS 2091 |
| Certificate | SGS Fimko Ltd |
| Conductor | Annealed solid copper wire |
| Insulation | Lead free PVC |
| Cabling | Cores twisted together |
| Filling | Lead free PVC |
| Sheath | Black lead free PVC |
| Application | Mainly for fixed surface installation at applications where the colour of the cable is not to be distinguished from the surface material. Not to be laid directly in the ground. |
| Operating temperature | max +70 °C |
| Handling temperature | min -15 °C |
| Packing | coil |

| Product number | Number of cores and nominal cross-section of conductors mm ² | Outer diameter of cable mm | Max. resistance of conductor at +20°C Ω/km | Total weight kg / km | Standard packing m |
|----------------|---|----------------------------|--|----------------------|--------------------|
| 0406596 | MMJ 3x1.5 S BLACK | 9.0 | 12.1 | 123 | 50 coil |
| 0406597 | MMJ 3x2.5 S BLACK | 10.0 | 7.41 | 161 | 50 coil |
| 0406598 | MMJ 5x1,5 S BLACK | 11.0 | 12.1 | 183 | 50 coil |
| 0406599 | MMJ 5x2,5 S BLACK | 12.5 | 7.41 | 259 | 50 coil |